



(43) International Publication Date  
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number  
WO 2004/112239 A1

BEST AVAILABLE COPY

(51) International Patent Classification<sup>7</sup>:  
3/21, 3/343, 1/02

H03F 1/30,

(74) Agent: ELEVELD, Koop, J.; Prof. Holstlaan 6, NL-5656  
AA Eindhoven (NL).

(21) International Application Number:

PCT/IB2004/050902

(22) International Filing Date: 15 June 2004 (15.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
03101789.0

18 June 2003 (18.06.2003) EP

(71) Applicant (for all designated States except US): KONIN-  
KLJKE PHILIPS ELECTRONICS N.V. [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): PRIKHODKO,  
Dmitry, P. [RU/NL]; c/o Prof. Holstlaan 6, NL-5656  
AA Eindhoven (NL). VAN BEZOOIJEN, Adrianus  
[NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven  
(NL). CHANLO, Christophe [FR/NL]; c/o Prof. Hol-  
stlaan 6, NL-5656 AA Eindhoven (NL). HUG, John, J.  
[US/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven  
(NL). KOSTER, Ronald [NL/NL]; c/o Prof. Holstlaan 6,  
NL-5656 AA Eindhoven (NL).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted  
a patent (Rule 4.17(ii)) for the following designations AE,  
AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ,  
CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE,  
EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS,  
JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,

[Continued on next page]

(54) Title: OUTPUT POWER DETECTION CIRCUIT



(57) Abstract: A detection circuit for detecting the output power of a power amplifier comprises a first current mirror transistor (T1) having a base, which is connectable to a power transistor (T10), and a collector, a RF detection means (RF-det) for detecting the RF current flowing through the current mirror transistor (T1). Said RF detection means (RF-det) is connected to the collector of said first current mirror transistor (T1). Said detection circuit further comprises a biasing means (bias-RF-det) for biasing said RF detection means (RF-det), wherein said biasing means is connected to said collector of said first current mirror (T1) and said RF